

CLEANING SEALING & AFTERCARE

SOLVEX TECHNICAL DATA SHEET

REF: 24/5/1 FEBRUARY 2021



LTP SOLVEX

High Performance Remover.

For interior & exterior use.

Removes silicone and acrylic waxes, adhesive polymers and epoxy grout residues.

For Stone, Travertine, Terracotta, Slate, Sandstone, Flagstones, Quarry Tiles, Glazed Ceramics and Porcelain.

A powerful non-caustic stripper that softens most types of surface sealer, which can then be removed with ease. Suitable for removing most wax, oil, silicone, acrylic, polyurethane sealers and residual epoxy grout. After washing and rinsing, surfaces are ideal for re-sealing.

Directions for use

For application and cleaning tools see LTP website.

Pour contents into a glass or metal container (not plastic). Apply generously by dabbing on with a cloth or brush. Work in manageable areas of no more than 5 sq metre and do not brush out. Leave for up to 30 minutes, but do not allow the solution to dry out. If drying should occur within 30 minutes apply a little more solution. Use a coarse, stiff brush or abrasive pad to remove softened coating from the surface. Repeat the process if unwanted material remains. Wash down with a dilute solution of LTP Grimex, rinse with plenty of water and leave to dry (min 24hrs) before re-sealing. Use natural fibre brushes. Brushes made from synthetic fibres may be damaged by this product. If you are unsure of correct application methods, test on an inconspicuous area, prior to general application. If removing residues from epoxy grout; apply making sure to avoid prolonged contact with the joint as well. Viscous solution should not drip if used on vertical surfaces. Protect acrylic surfaces such as baths and shower trays from contact.

Coverage

Light Stripping 8-10m²/litre

Deep Stripping 5m²/litre

Storage information

Store in a cool, dry, frost-free environment.

Shelf Life – Up to 5 years

Health, Safety & Environmental

CONTAINS: Benzyl Alcohol; Silicic Acid, Lithium Magnesium Sodium Salt; (L) C9-11 Pareth-9
Causes serious eye irritation.

Harmful if swallowed or if inhaled.

Keep out of reach of children. Do not breathe vapour/spray. Wash contaminated skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in well ventilated area. IF SWALLOWED: Immediately call a POISON CENTRE/doctor. IF INHALLED: Remove person to fresh air and keep comfortable for breathing IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Dispose of contents/container to a waste collection point in accordance with local regulations.



WARNING



This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area.



For any LTP product information call our technical helpline
+ 44 (0) 1823 666213 | www.ltp-online.co.uk | technical@ltp-online.co.uk
Tone Est, Milverton Road, Wellington, Somerset, TA21 0AN

